

SEWAGE PUMP E7055



½ HP − 5,340 GPH @ 10ft



Models Available:

E7055-NS: (No switch - pump only)

E7055-VS: (No controller - pump and vertical switch only) E7055-VSC1.5: (Includes enhanced controller with vertical float switch) E7055-VSC2: (Includes deluxe controller with vertical float switch) E7055-VSC3: (Includes high-cycle controller with vertical float switch)

E7055-TS: (No controller - pump and tether switch only) E7055-TSC1.5: (Includes enhanced controller with tether switch) E7055-TSC2: (Includes deluxe controller with tether switch) E7055-TSC3: (Includes high-cycle controller with tether switch)



REMOTE Notification

Industrial Grade for the Residential Market

www.StopFlooding.com

800-991-0466



SEWAGE PUMP E7055

Features and Construction

- Cast-iron construction
- Continuous-duty rated
- Energy-efficient permanent split capacitor (PSC) motor
- · Handles 2-inch solids with 2-inch discharge
- · Thermally protected
- · Water-cooled motor (no cooling oil)
- · Electroplated steel shaft
- · Upper and lower sealed ball bearings
- · Cast-iron vortex impeller
- Dual Carbon/ceramic seals plus (1) Buna-N-Seal
- 10-foot pump cord


Mix and Match Ordering

You have the flexibility to order any pump with any switch.

- Option 1: Order a pump and a switch as separate items.
- **Option 2**: Order as a prepackaged system with any switch in a single carton, ready for delivery.

Switches and Controllers Comparison


Includes: Manual and stainless-steel hose clamp	Standard Enhanced Deluxe High-Cycle			
	VS TS	VSC1.5 TSC1.5	VSC2 TSC2	VSC3 TSC3
Sounds an alarm and alerts when:				
AC power has failed			٠	٠
Pump or float problem is detected			٠	•
9V battery is low or slide switch is off			٠	٠
Remote Notification Connections: (Allows for connection of external devices)				
USB Data Port (Can send specific email, text, or push notifications)			٠	•
Remote Terminal (Allows for connection to home security or other dry contact device)			•	•
Float switch can be unplugged from controller for easy installation		•	•	•
System operating light (flashes)		•	•	•
Adjustable run time from 5-45 seconds after the float drops		•	•	•
Activates pump weekly to exercise and extend pump life		٠	٠	•
Universal controller mounting tabs		٠	•	•
2-foot power cord		•		
4-foot power cord			٠	٠
10-foot float switch cord	٠	٠	٠	•
Piggyback plug	٠	٠	٠	٠
High water accessory available			•	
Designed for high-cycle applications				•



Specifications and Dimensions

Flow @ 0 ft Head	7,680 GPH/128 GPM
Flow @ 10 ft Head	5,340 GPH/89 GPM
Max Head	23 ft (7 m)
Discharge	2 in (5.1 cm)
Motor HP/Type	1/2 HP PSC Motor
Voltage	115 VAC, 60 Hz
Amp Draw @ 10 ft Head	7 Amps
Width	9 in (22.9 cm)
Depth	5.875 in (16.5 cm)
Height	16.5 in (48.3 cm)
Weight	37 lb (16.8 kg)

Flow Chart



Why Pro Series Pumps

Premium Components

- Designed for higher pumping capacity and increased energy efficiency, resulting in proven reliability
- · Industrial grade built for the residential market
- PSC motors
- Upper and lower ball bearings

Exceeding Expectations

- Patented switches and controllers with state-of-the-art monitoring systems
- "Good, Better, Best" offering allows for a wide range of products to best fit your needs

On the Forefront of Technology

- Many models within the Pro Series line have a USB data port and remote terminal which allows for connection to an external device that can notify a homeowner if a problem arises or maintenance is needed
- Receive text, email, or push notifications to keep you in the know while on the go

Available from: